

MATERIAL SAFETY DATA SHEET

According to 29 CFR 1910.1200(g)



Date Issued: 11/17/2009
 MSDS No: 15
 Date-Revised: 03/01/2010
 Revision No: 2

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: Automotive Paste Wax
PRODUCT FORMULATION NAME: E-Z Wax® Paste-Yellow

MANUFACTURER

Auto Wax - An ITW Company
 Auto Magic®
 1275 Round Table Drive
 Dallas, TX 75247
Product Stewardship: 1-800-826-0828
Transportation: 1-800-826-0828
Service Number: 1-214-631-4000
 Auto Wax - An ITW Company
 Auto Magic®

24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-826-0828

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW****IMMEDIATE CONCERNS:** Harmful if swallowed.**POTENTIAL HEALTH EFFECTS****EYES:** Moderately irritating to the eyes.**SKIN:** Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).**INGESTION:** Harmful if swallowed.**INHALATION:** Prolonged or excessive inhalation may cause respiratory tract irritation.**SIGNS AND SYMPTOMS OF OVEREXPOSURE****ACUTE TOXICITY:** May cause headaches and dizziness.**MEDICAL CONDITIONS AGGRAVATED:** dermatitis may be aggravated by excessive exposure to skin.**ROUTES OF ENTRY:** include skin contact, eye contact and ingestion**TARGET ORGAN STATEMENT:** not established**CANCER STATEMENT:** not established**3. COMPOSITION / INFORMATION ON INGREDIENTS**

| Chemical Name | Wt.% | CAS |
|--|---------|------------|
| Odorless Mineral Spirits | 40 - 50 | 64742-48-9 |
| Kerosine (petroleum) (Kerosene) | 5 - 10 | 8008-20-6 |
| Distillates (petroleum) hydrotreated light | 10 - 20 | 64742-47-8 |

4. FIRST AID MEASURES**EYES:** Flush eye with water for 15 minutes. Seek medical attention if irritation persists.**SKIN:** Wash with soap and water.**INGESTION:** Do not induce vomiting. Seek medical attention immediately.**INHALATION:** Move to fresh air**5. FIRE FIGHTING MEASURES****FLASHPOINT AND METHOD:** ~ 43°C (109°F) TCC**FLAMMABLE LIMITS:** not available**AUTOIGNITION TEMPERATURE:**

Notes: not established

GENERAL HAZARD: Combustible liquid. Keep away from heat and open flame.

EXTINGUISHING MEDIA: use foam, dry chemical or carbon dioxide extinguisher

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide and Carbon Dioxide

EXPLOSION HAZARDS: not established

FIRE FIGHTING PROCEDURES: not established

SENSITIVE TO STATIC DISCHARGE: not established

SENSITIVITY TO IMPACT: not established

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain and collect with absorbent

LARGE SPILL: LARGE SPILLS: Shut off leak if safe to do so. Contain material to avoid run off and collect spill with absorbent. Proper disposal of absorbent is required after use.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep out of reach of Children.

STORAGE TEMPERATURE: 4°C (40°F) Minimum to 35°C (95°F) Maximum

SHELF LIFE: one year

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

| OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200) | | | |
|---|------------|-----------------|------------------------|
| | | EXPOSURE LIMITS | |
| | | Supplier OEL | |
| Chemical Name | | ppm | mg/m ³ |
| Odorless Mineral Spirits | TWA | 300 ppm | 1900 mg/m ³ |
| Kerosine (petroleum) (Kerosene) | TWA | 400 ppm | |
| Distillates (petroleum) hydrotreated light | TWA | 300 ppm | 2300 mg/m ³ |

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields or goggles.

SKIN: Use Nitrile/ Vinyl gloves

RESPIRATORY: NIOSH respirator -(organic vapor) in absence of proper environmental control.

PROTECTIVE CLOTHING: Clean, body-covering clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

| Chemical Name | Flash Point (°C) | Boiling Point (°C) | Specific Gravity |
|--|------------------|--------------------|------------------|
| Odorless Mineral Spirits | 49 | 178 | 0.76 |
| Distillates (petroleum) hydrotreated light | 81 | 218 | 0.79 |

PHYSICAL STATE: Solid

ODOR: hydrocarbon odor

APPEARANCE: Yellow Paste

PERCENT VOLATILE: 75-85

MELTING POINT: > 80°C (180°F)

FLASHPOINT AND METHOD: ~ 43°C (109°F) TCC

SPECIFIC GRAVITY: ~ 0.800 to 0.9 gm/ml

(VOC): < 45.000 % by weight

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

11. TOXICOLOGICAL INFORMATION

ACUTE

| Chemical Name | ORAL LD ₅₀ (rat) | DERMAL LD ₅₀ (rabbit) |
|--|--------------------------------|-------------------------------------|
| Distillates (petroleum) hydrotreated light | > 5 g/Kg-rat | > 3.16 g/kg - rabbit |

CARCINOGENICITY

IARC: Listed by IARC- NO

NTP: Listed by NTP- NO

OSHA: Listed by OSHA- NO

SENSITIZATION: not available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: not available

ECOTOXICOLOGICAL INFORMATION: not available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with local, state, and federal laws.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Paint related material

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN1263

PACKING GROUP: III

OTHER SHIPPING INFORMATION: Refer to bill of lading or container label for DOT or other transportation hazard classification, if any.

15. REGULATORY INFORMATION

UNITED STATES

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All Ingredients are on the TSCA Inventory or are not required to be listed on the TSCA Inventory

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic



Combustible Liquid

16. OTHER INFORMATION


PREPARED BY: Tony Casmus

REVISION SUMMARY: Revision #: 2. This MSDS replaces the March 01, 2010 MSDS. ,

HMIS RATING

| | | |
|-----------------------------|---|---|
| HEALTH: | - | 1 |
| FLAMMABILITY: | | 2 |
| PHYSICAL HAZARD: | | 0 |
| PERSONAL PROTECTION: | | |

NFPA CODES



MANUFACTURER DISCLAIMER: The information in this MSDS was obtained from current and reputable sources. However, the data is provided without any warranty, express or implied, regarding its correctness or accuracy. It is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.