

Safety Data Sheet

Product Name: ULTRA SHINE TIRE DRESSING - 501105

Product identifier: 501105

Revision Date: 08-19-2016

Replaces:



1. Identification

Product identifier used on the label:

Product Name: **ULTRA SHINE TIRE DRESSING - 501105**

Product identifier: 501105

Other means of identification

Synonyms: No data available

Recommended use of the chemical and restrictions on use: Ketone Solvent

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Chemical Manufacturer /
Importer / Distributor: ITW Evercoat
a division of Illinois Tool Works Inc.
6600 Cornell Road
Cincinnati, OH 45242
513-489-7600

Emergency phone number: CHEMTREC: 1-800-424-9300
CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Classification: Not classified as hazardous under GHS

GHS Hazard Statements: No hazard statements required

Hazards not otherwise classified: No data available

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Acetone	67-64-1	1 - 5
Hyrotreated Heavy Naphthe	68551-16-6	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Safety Data Sheet

Product Name: ULTRA SHINE TIRE DRESSING - 501105

Product identifier: 501105

Revision Date: 08-19-2016

Replaces:

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Eye Contact: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing. Flush eyes gently with water for at least 15 minutes, lifting upper & lower eye lids. Seek immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Remove contaminated clothing and continue flushing with water. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist. Wash clothing before reuse.

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately. If symptoms develop, immediately move individual away from exposure and into fresh air. Get medical attention immediately. Keep the victim warm and quiet. If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice.

Ingestion: Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical attention immediately. Provide medical care provider with this MSDS. Call a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical personnel. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. If possible, do not leave individual unattended.

Most important symptoms/effects, acute and delayed:

Most important symptoms/effects (Acute): No data available

Most important symptoms/effects (Delayed): No data available

Indication of immediate medical attention and special treatment needed, if necessary: No additional first aid information available

Safety Data Sheet

Product Name: ULTRA SHINE TIRE DRESSING - 501105

Product identifier: 501105

Revision Date: 08-19-2016

Replaces:

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire.

Unsuitable extinguishing media: No data available

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Fire and/or Explosion Hazards: Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Material will burn in a fire.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide, Formaldehyde, Silicon dioxide, Toxic and corrosive gases,, Carbon dioxide, Carbon monoxide, Hydrocarbons

Special protective equipment and precautions for fire-fighters: Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Use methods for the surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

Methods and materials for containment and cleaning up: No special spill clean-up considerations. Collect and discard in regular trash.

Safety Data Sheet

Product Name: ULTRA SHINE TIRE DRESSING - 501105

Product identifier: 501105

Revision Date: 08-19-2016

Replaces:

7. Handling and storage

Precautions for safe handling: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid breathing vapors or mists. Do not take internally. Keep container closed when not in use. Keep out of the reach of children.

Conditions for safe storage, including any incompatibilities

Conditions for safe storage: Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Store in a cool dry place For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact with incompatible materials.

Materials to Avoid/Chemical Incompatibility: Strong oxidizing agents Strong acids Strong alkalis Hydrogen peroxide

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Acetone	1000 ppm	500 ppm	750 ppm

Appropriate engineering controls: No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.

Individual protection measures, such as personal protective equipment:

Eye Protection: Wear safety glasses when handling this product. Wear goggles and a Face shield Splash proof chemical goggles are recommended to protect against the splash of product.

Skin Protection: Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and

Safety Data Sheet

Product Name: ULTRA SHINE TIRE DRESSING - 501105

Product identifier: 501105

Revision Date: 08-19-2016

Replaces:

water before eating, drinking, and when leaving work. Where use can result in skin contact, practice good personal hygiene. Use of protective coveralls and long sleeves is recommended. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots

Respiratory Protection:

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors.

Other Protective Equipment:

Wear goggles and a Face shield Splash proof chemical goggles are recommended to protect against the splash of product. Where use can result in skin contact, practice good personal hygiene. Use of protective coveralls and long sleeves is recommended. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots

9. Physical and chemical properties

Appearance (physical state, color, etc.):

Appearance (physical state):	No data available
Color:	No data available
Odor:	No data available
Odor threshold:	No data available
pH:	No data available
Melting Point/Freezing Point (°C):	No data available
Initial Boiling Point and Boiling Range (°C):	No data available
Flash Point (°C):	No data available
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper/lower flammability or explosive limits:	
Upper Flammable/Explosive Limit (%):	No data available
Lower Flammable/Explosive Limit (%):	No data available
Vapor Pressure:	No data available
Vapor Density:	No data available
Relative Density:	Not determined
Solubility(ies):	No data available

Safety Data Sheet

Product Name: ULTRA SHINE TIRE DRESSING - 501105

Product identifier: 501105

Revision Date: 08-19-2016

Replaces:

Partition coefficient: n-octanol/water:	No data available
Auto-ignition Temperature (°C):	No data available
Decomposition Temperature:	No data available
Viscosity:	No data available

10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	No data available
Conditions to avoid (e.g., static discharge, shock, or vibration):	Sparks, open flame, other ignition sources, and elevated temperatures. Contamination
Incompatible materials:	Strong oxidizing agents Strong acids Strong alkalis Hydrogen peroxide
Hazardous decomposition products:	Carbon dioxide Carbon monoxide Formaldehyde Silicon dioxide Carbon dioxide Carbon monoxide Hydrocarbons

11. Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):	Inhalation, Ingestion, Skin contact, Eye contact, Absorption
Symptoms related to the physical, chemical and toxicological characteristics:	No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache and dizziness. Airborne overexposure well above the PEL may result additionally in eye irritation, headache, chemical bronchitis, asthma-like findings or pulmonary edema.
Inhalation Toxicity:	Non-Toxic. Not known to cause systemic damage.
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption:	No absorption hazard in normal industrial use. Causes skin irritation. Contact may cause irritation and possible dermatitis or sensitization. Symptoms may include redness, burning, drying and cracking of skin, and skin burns
Eye Contact:	Can cause minor irritation, tearing and reddening. Contact with liquid or vapor may result in irritation, redness, tearing, and blurred vision.

Safety Data Sheet

Product Name: ULTRA SHINE TIRE DRESSING - 501105

Product identifier: 501105

Revision Date: 08-19-2016

Replaces:

Ingestion Irritation: Mildly irritating to mouth, throat, and stomach. Can cause abdominal discomfort. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible ulcerations to mucous membranes. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. May also cause effects on the liver and kidneys.

Ingestion Toxicity:

Long-Term (Chronic) Health Effects:

Carcinogenicity: None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA. Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.

Reproductive and Developmental Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

Skin Contact: Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Skin Absorption: Upon prolonged or repeated exposure, no hazard in normal industrial use.

Numerical measures of toxicity (such as acute toxicity estimates)

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	Oral LD50 Rat 5800 mg/kg	Dermal LD50 Rabbit 20000 mg/kg	Inhalation LC50 (4h) Rat > 16000 ppm

Whether the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available	N	N	N

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available): This material is not expected to be harmful to the ecology.

Persistence and degradability: No data available

Bioaccumulative potential: No data

Mobility in soil: No data available

Other adverse effects (such as hazardous to the ozone layer): No data available

Safety Data Sheet

Product Name: ULTRA SHINE TIRE DRESSING - 501105

Product identifier: 501105

Revision Date: 08-19-2016

Replaces:

Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Acetone	Aquatic EC50 (48h) Daphnia 10294 - 17704 MG/L		Aquatic LC50 (96h) Rainbow Trout 4740 - 6330 MG/L

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

Description of waste residues: Spent or discarded material is a hazardous waste.

Waste treatment methods (including packaging): Dispose of in a landfill. Disposal is not likely to be regulated.

Waste Disposal Code(s): D001 U002 acetone

14. Transport information

UN number: No data available

UN proper shipping name: Not Regulated

Transport hazard class(es): No data available

Packing group: No data available

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

TSCA Status: The intentional ingredients of this product are listed.

Regulated Components

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Acetone	67-64-1	N	N	Y	N

16. Other information, including date of preparation or last revision.

Revision Date: 08-19-2016

Revision Number: 9

Safety Data Sheet

Product Name: ULTRA SHINE TIRE DRESSING - 501105

Product identifier: 501105

Revision Date: 08-19-2016

Replaces:

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances