

Product Technical Bulletin

PRODUCT NAME:

Clay Magic® Polymer Detailing Clay Bar

PART #:

CM3200
(Polymer Clay)

PACKAGE:

200 gram bar

PRODUCT CATEGORY:

Surface Preparation

COLOR:

White

SCENT:

N/A

ABRASIVENESS:

0.5 out of 10 (10 is highest amount of abrasive)

PRODUCT DESCRIPTION:

Clay Magic® Polymer Clay is an advanced clay that contains an embedded polymer that helps to glide the bar over surfaces better than ever. These polymers also add a layer of surface protection and shine to your finish. It's ideal for use before and between regular wax jobs. Polymer Clay is softer than other clay bars, which makes it easier than ever to mold and form. It removes harmful surface contaminants such as paint overspray, tree sap, bug residue, industrial fallout, bird droppings, and other stubborn dirt. Polymer Clay is safe on all paint, chrome, glass, fiberglass and plastic. Use it with Clay Lube.

DIRECTIONS:

Form Clay Magic® into an oval shape. Spray Clay Magic® Clay Lube onto a 3'x3' section of a clean, cool and dry surface. Gently rub the clay bar over the area using a back-and-forth motion in 5 to 6 passes. Wipe the surface dry. To clean the clay bar, simply fold it in half and reshape into an oval shape. Store the clay bar in a clay container or plastic baggie with a light spray of lubricant. **DISCARD BAR IF DROPPED ON THE GROUND.**

SURFACE APPLICATIONS:

Refinished paint, factory paints, clear coats, acrylics, enamels, and lacquer paints. It can also be used on glass, chrome, fiberglass, plastic, and many other smooth hard surfaces for contamination and paint overspray removal.

HELPFUL TIPS:

Always make sure the surface you intend to clay is thoroughly washed, dried, and cool. Fold the clay frequently to ensure clean clay is used. It is best to fold the clay after each main body panel is completed. Most of the contamination removal is going to be on the upper portions of the vehicle (above the side moldings). Do not use clay without a clay lubricant. The lubricant helps glide the clay and loosen imbedded surface debris. Do not use the clay if dropped on the ground. This collected dirt may add surface scratches.

SAFETY & HANDLING:

Safety Data Sheets can found online at automagic.com

