

PRODUCT: EVER-GLAZE & SPOT PUTTY

PART NUMBER: 100403 1 lb. Tube 12 units/case

DESCRIPTION: EVER-GLAZE is a nitrocellulose, single component spot putty to fill sand scratches, file marks and other imperfections, not completely filled by the primer surfacer. Fast drying and easy sanding. Shrink-resistant formula. Dries smooth. Superior color holdout.

APPROVED SUBSTRATES:

- Sanded Body Filler
- Cured sanded primer

PREPARATION: Use 180 grit or finer to prepare surface.

APPLICATION:

- Using a flexible putty knife or plastic spreader, apply material in several thin coats.
- Work quickly to prevent material from rolling due to fast drying.
- Allow a five minute dry time between coats

FINISH: Sand with 180 grit or finer sandpaper.
Heavy applications require a longer dry to sand time

TOPCOAT: Apply 2K polyester, 2K urethane, 2K epoxy, or 1K primer to manufacturer's recommendations

TECHNICAL SPECIFICATIONS:

- | | |
|--------------------|---------------------------------------------|
| ▪ Appearance | Red Oxide Paste |
| ▪ VOC | Refer to Section 9 of the Safety Data Sheet |
| ▪ Relative Density | Refer to Section 9 of the Safety Data Sheet |
| ▪ Sand Time | 30-40 min. |

NOTE: Properties are typical values and should not be considered as sales specifications. Physical testing performed @ ~72°F (22°C) / 75% RH unless otherwise noted.

SAFETY & HANDLING:

Read all directions and warnings prior to using Evercoat® products. Safety Data Sheets can be found online at evercoat.com.

NOTES: Keep tube closed and store in a cool dry place